



SPECIFICATIONS
 Rated Current: 1.0AMP
 Contact Resistance: 20mΩ Max
 Withstand Voltage: 500V AC/DC
 Insulation Resistance: 1000MΩ Min
 Operation Temperature: -40°C to +105°C

Contact Material: Brass
 Contact Plating: Au or Sn Over Ni
 Insulator Material: Polyester (UL94V-0)
 Standard: PA6T
 Max. Processing Temp: 230°C for 30-60 seconds
 (260°C for 10 seconds)

| Dimension antitheses list | | | | | |
|---------------------------|------|------|------|-------|-------|
| ITEM | PA | PB | PC | L短 | L长 |
| Standard | 3.00 | 4.90 | 3.20 | 10.50 | 13.00 |
| Alternate | | | | | |

| | | | | |
|------------|----|-----------|--------------|--------------------------------|
| Dwg. No. | | 13D000008 | | 1.27mm PH H1.0mm 2xNPin 90° |
| Projection | | | | |
| Unit | mm | Scale | NOT TO SCALE | |
| Type | PH | Sheet | 1/1 | |

| | | | |
|-----------------|-------------|---------|-----|
| 震导 hnndo | | | |
| P/N | 1321XX33001 | | |
| Date | 2025/8/1 | Ver. NO | 1.0 |